



## Swift<sup>®</sup> hardener 9502

**Type of Adhesive** Cross linker/hardener based on Isocyanate for 2C solvent based adhesives based on Polyurethane, Polychloroprene and Nitrile.

**Product Benefits**

- slow-curing
- long pot life
- non flammable

**Typical Applications** Second component for 2C-adhesives in the shoe industry (bonding of elements of the shoe: leather, rubber, synthetic materials) and for conveyor belts (adhesion of rubber).

**Suitable substrates** Not applicable, depends on the suitable adhesive.

### Typical Properties

Property	Value
Polymer base	isocyanate
Colour / Appearance	brown / liquid
Solids content	approx. 30%
Density at 20°C	approx. 1.290 g/cm <sup>3</sup>
NCO-content	8 to 9%
Shelf life	12 months



# H.B. Fuller



## TECHNICAL DATA SHEET

<b>Application Instructions</b>	Mixing ratio, pot life and setting time are given in the Technical Data Sheet of the suitable adhesive.
<b>Cleaning Instructions</b>	Please contact your local Sales Office for available cleaning solutions.
<b>Typical Packaging</b>	Please contact your local Sales Office for available packaging options.
<b>Storage Conditions</b>	In original sealed packaging protected from sun, dust, moisture and high temperatures. Clean and dry conditions above 10°C and below 30°C. Sensitive to cold, crystallization at temperatures below 10°C, under light heating transition to solution. Sensitive to humidity.
<b>Disposal Advice</b>	Please refer to the MSDS for disposal instructions.
<b>Safety Advice</b>	Please refer to the MSDS for safety advice.

### Our Focus is Clear. Perfecting Adhesives.

**IMPORTANT:** The information, specifications, procedures and recommendations herein (together "information") are based on our experience and we believe these to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that the information will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

**NOTE TO USER:** by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.



## H.B. Fuller

**H.B. Fuller Company**

info-europe@hbfuller.com  
www.hbfuller.com/  
eimea/contact-us