

TECHNICAL DATA SHEET

MATRX PERMANENT ADHESIVE (GD-31)

TYPE:	PERMANENT PRESSURE SENSITIVE HOTMELT ADHESIVE
PROPERTIES:	COLOUR: AMBER TINT – ODOUR: NONE
SUGGESTED USE:	PAPER, PLASTIC, WOOD, METAL, ETC...
CHARACTERISTICS:	EXCELLENT TACK AND COHESIVE STRENGTH. VERY STRONG SHEAR & PEEL QUALITIES. GOOD HIGH TEMPERATURE RESISTANCE.
TEMPERATURE RANGE:	10°C TO 60°C. DUE TO VARIATION IN THE SIZE OF THE MATRX PATTERNS, AND NATURE OF THE TESTING, RESULTS SHOULD BE TREATED AS APPROXIMATE.
SUGGESTED HANDLING:	READY FOR USE AS SUPPLIED. KEEP AWAY FROM DUST, OIL, AND ULTRAVIOLET LIGHT
SHELF LIFE:	USE OLDEST STOCK FIRST. THIS PRODUCT SHOULD BE STORED IN A DUST FREE ENVIRONMENT AND IN A COOL DRY PLACE. DISCARD UNUSED PRODUCT AFTER 18 MONTHS. THIS PRODUCT CONTAINS SOME OIL.

We are available to help purchasers obtain best results from information believed to be reliable. However we have no control over the conditions under which our products are transported, stored, handled or used by Purchasers and in any event all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use.