



Swift[®] prime 2903

Type of Adhesive Solvent based primer for metals.

Product Benefits

- short drying time
- good adhesion to metals

Typical Applications Adhesion promoter for bonding rubber materials to metal, especially steel.

Suitable substrates Metal, especially steel.

Typical Properties

Property	Value
Base	synthetic resin
Colour	black
Density	approx. 0,85 +/- 0,01 g/cm ³
Viscosity (Brookfield, at 20°C)	approx. 500 mPa.s
Shelf life	18 months



Application Instructions	<p>Stir well before using!</p> <p>Application method: Brush Consumption: approx. 150 – 200 g/cm²</p> <p>Apply this product to clean metal surfaces with a thin and even coat. After a drying time of 30 minutes the bonding can be carried out within 24 hours with one of our adhesives for conveyor belt area.</p>
Cleaning Instructions	<p>Please contact your local Sales Office for available cleaning solutions.</p>
Typical Packaging	<p>Please contact your local Sales Office for available packaging options.</p>
Storage Conditions	<p>In original sealed packaging protected from sun, dust, moisture and high temperatures. Clean and dry conditions above +10°C and below +30°C.</p>
Disposal Advice	<p>Please refer to the MSDS for disposal instructions.</p>
Safety Advice	<p>Please refer to the MSDS for safety advice.</p>

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: The information, specifications, procedures and recommendations herein (together "information") are based on our experience and we believe these to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that the information will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.



H.B. Fuller

H.B. Fuller Company

info-europe@hbfuller.com
www.hbfuller.com/
eimea/contact-us