



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *swift@prime 2903*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC1 Adhesives, sealants
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*H.B. Fuller, Isar-Rakoll, S.A.
 Estrada Nacional 13
 PT-4486-851 Mindelo - Vila do Conde
 +351 229 288 200
 EU-MSDS@hbfuller.com*
- **Informing department:** Regulatory department
- **1.4 Emergency telephone number:**
*NCEC emergency service
 +44 (0) 1235 239 670 (24 hours)*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

	
GHS02	GHS07
- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
*4-methylpentan-2-one
 Butan-2-one*
- **Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: swift@prime 2903

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:**
Primer
Adhesive.

- **Dangerous components:**

CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-0000	Butan-2-one Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
EC number: 926-605-8 Reg.nr.: 01-2119486291-36-0000	HYDROCARBONS, C6-C7, ISOALKANES, CYCLIC, <5% n-HEXANE Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	5-10%
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119489801-30-0000	Carbon black substance with a Community workplace exposure limit	<2.5%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-0000	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	<0.5%
CAS: 108-95-2 EINECS: 203-632-7	phenol Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Muta. 2, H341; STOT RE 2, H373; Skin Corr. 1B, H314	<0.5%
CAS: 8052-10-6 EINECS: 232-484-6	Rosin Skin Sens. 1, H317	<0.2%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information**
Instantly remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Take affected persons into the open air.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 2)

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, sand, extinguishing powder. Do not use water.
Use fire fighting measures that suit the environment.
Water haze
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Can be released in case of fire
Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter drains.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Send for recovery or disposal in suitable containers.
Do not use tools that can cause ignition.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Store in cool, dry place in tightly closed containers.
- Ensure good ventilation/exhaustion at the workplace.
- Take note of emission threshold.
- Use solvent-proof equipment.
- Keep out of the reach of children.

Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

- Protect against electrostatic charges.
- Highly volatile, flammable constituents are released during processing.
- Fumes can combine with air to form an explosive mixture.
- Flammable mixtures may be formed in empty containers.

7.2 Conditions for safe storage, including any incompatibilities

- **Storage**
- **Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
 - Protect from heat and direct sunlight.
 - Store in cool, dry conditions in original sealed container
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

8.1 Control parameters

- **Components with limit values that require monitoring at the workplace:**

108-10-1 4-methylpentan-2-one	
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV
78-93-3 Butan-2-one	
WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
1333-86-4 Carbon black	
WEL	Short-term value: 7 mg/m ³ Long-term value: 3.5 mg/m ³
108-88-3 toluene	
WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
108-95-2 phenol	
WEL	Short-term value: 16 mg/m ³ , 4 ppm Long-term value: 7.8 mg/m ³ , 2 ppm Sk

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 4)

- **DNELs**

Ethylmethylketon CAS 78-93-3

Anwendungsbereich: Arbeitnehmer

Expositionswege: Hautkontakt

Mögliche Gesundheitsschäden: Langzeit - systemische Effekte

Wert: 1161 mg/kg

Anwendungsbereich: Arbeitnehmer

Expositionswege: Einatmen

Mögliche Gesundheitsschäden: Langzeit - systemische Effekte

Wert: 600 mg/m³

- **PNECs**

Butanon CAS 78-93-3

Meerwasser Wert: 55,8 mg/l

Süßwassersediment Wert: 284,74 mg/kg

Meeressediment Wert: 287,7 mg/kg

Boden Wert: 22,5 mg/kg

Süßwasser Wert: 55,8 mg/l

- **Ingredients with biological limit values:**

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L

Medium: urine

Sampling time: post shift

Parameter: 4-methylpentan-2-one

78-93-3 Butan-2-one

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift

Parameter: butan-2-one

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Breathing equipment:** Use breathing protection in case of insufficient ventilation.

- **Recommended filter device for short term use:** Combination filter A-P2

- **Protection of hands:**



Protective gloves.

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 5)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed safety glasses.

- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	80 °C (DIN 53171)

· **Flash point:** <0 °C (DIN 53213)

· **Inflammability (solid, gaseous)** Not applicable.

· **Decomposition temperature:** Not determined.

· **Self-inflammability:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Critical values for explosion:

Lower:	0.7 Vol % (EN 1839)
Upper:	11.5 Vol % (EN 1839)

· **Vapour pressure at 20 °C:** 105 hPa (DIN 51640)

· **Density at 20 °C** 0.85 g/cm³ (DIN 51757)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

dynamic at 20 °C:	Ca. 600 mPas (Brookfield (ISO 2555))
kinematic:	Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: swift@prime 2903

(Contd. of page 6)

- | | |
|--------------------------------|--|
| · Solvent content: | |
| Organic solvents: | 75.6 % |
| Solids content: | 24.4 % (ISO 3251) |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Develops readily flammable gases / fumes
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

108-10-1 4-methylpentan-2-one

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	>16,000 mg/kg (rab)
Inhalative	LC50/4h	8.3-16.6 mg/l (rat)

78-93-3 Butan-2-one

Oral	LD50	>2,600 mg/kg (rat)
Dermal	LD50	>8,000 mg/kg (rbt)
Inhalative	LC50/2h	40 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

108-10-1 4-methylpentan-2-one

LC50/96h	505-540 mg/l (Pimephales promelas)
IC50/96h	400 mg/l (Selenastrum capricornutum)
EC50/48h	170 mg/l (Daphnia magna)

78-93-3 Butan-2-one

LC50/96h	3,220 mg/l (Pimephales promelas)
EC50/48h	5,091 mg/l (Daphnia magna)

12.2 Persistence and degradability

108-10-1 4-methylpentan-2-one

Bio.Abbaubark./14 d | 99 % (-)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Harmful to fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019


Version number 4

Revision: 18.06.2018

Trade name: swift@prime 2903

(Contd. of page 8)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	UN1133	
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 	1133 ADHESIVES, special provision 640D ADHESIVES	
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	II	
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	No	
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category 	Warning: Flammable liquids. 33 F-E, S-D A	
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.	
· Transport/Additional information:		
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	2 D/E	
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1133 ADHESIVES, SPECIAL PROVISION 640D, 3, II	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **National regulations**

- **Technical instructions (air):**

Class	Share in %
I	0,1-1
NK	50-100

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **VOC (EU) %** 75.69 %
- **Code MAL** 5-5
- **VOC (EU)** 643.3 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

- **Contact:** EU-MSDS@hbfuller.com

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: swift@prime 2903

(Contd. of page 10)

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Muta. 2: Germ cell mutagenicity – Category 2**Repr. 2: Reproductive toxicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

-GB-

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: **swift@prime 2903**

(Contd. of page 11)

Annex: Exposure scenario

- **Short title of the exposure scenario** butanone (CAS 78-93-3)
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC1 Adhesives, sealants
- **Process category**
 - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
 - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
 - PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
 - PROC4 Chemical production where opportunity for exposure arises
 - PROC5 Mixing or blending in batch processes
 - PROC7 Industrial spraying
 - PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
 - PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
 - PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
 - PROC10 Roller application or brushing
 - PROC13 Treatment of articles by dipping and pouring
 - PROC14 Tableting, compression, extrusion, pelletisation, granulation
 - PROC15 Use as laboratory reagent
- **Environmental release category**
 - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency**
 - 5 workdays/week.
 - 8hrs (full working shift).
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
 - Avoid contact with eyes.
 - Take precautionary measures against static discharge.
 - Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** Keep out of the reach of children.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
 - The usual precautionary measures should be adhered to general rules for handling chemicals.
 - Keep away from foodstuffs, beverages and food.
 - Take off immediately all contaminated clothing
 - Wash hands during breaks and at the end of the work.
 - Avoid contact with the eyes and skin.
 - Use breathing protection in case of insufficient ventilation.
- **Organisational protective measures** Deploy only trained chemical workers.
- **Technical protective measures**
 - Provide explosion-proof electrical equipment.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.01.2019

Version number 4

Revision: 18.06.2018

Trade name: swift@prime 2903

(Contd. of page 12)

Ensure that suitable extractors are available on processing machines

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed safety glasses.

Protective gloves.

· **Measures for consumer protection**

Ensure adequate labelling.

Keep locked up and out of the reach of children.

· **Environmental protection measures**

· **Water** *No special measures required.*

· **Disposal measures** *Disposal must be made according to official regulations.*

· **Disposal procedures**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Waste type** *Partially emptied and uncleaned packaging*

· **Exposure estimation**

· **Worker (dermal)** *The calculated value is smaller than the DNEL.*

· **Worker (inhalation)** *The calculated value is smaller than the DNEL.*

· **Consumer** *Not relevant for this Exposure Scenario.*

· **Guidance for downstream users** *No further relevant information available.*

GB