

**GARD**

# **GARDEX**

## **HOT MELT ANTI-ADHESION COMPOUND**

### **DESCRIPTION**

GARDEX hot melt release agent is a unique formulation developed to benefit any industry that uses hot melt adhesive. The unwanted build-up of hot melt is a common problem leading to machine downtime and therefore loss of production. Temperature stable up to 220 °C  
NSF Approved: Nonfood Compounds Program Listed (H1) 148386

### **AREAS OF APPLICATION**

GARDEX can be used to coat the inside of all hot melt glue pots on edge banders and all melt tanks within a hot melt glue system, also use to protect daubers, drive chains, drive shafts, screw threads, temperature probes, universal joints etc.

### **PACKAGING INDUSTRY**

Use on all areas around glue systems including pots, nozzles, modules, hoses, chains, drainage points etc.

### **WOODWORKING INDUSTRY**

Apply GARDEX to all edgebanders and associated equipment.

### **ECONOMICAL**

Only a fine coating of GARDEX is required to treat areas. Treated glue pots stay protected for up to six months. A little goes a long way !!!

### **EASY TO USE**

Simply apply GARDEX with a clean cloth or sponge to all areas that become contaminated with hot melt. (NB. Do not apply to guide rails/belts etc.)

(Easy to follow instructions are on every pack)



**Non Citrus  
Based**



**Food  
Approved**



**Non  
Flammable**



**Safety  
In Use**



**Non Hazardous  
for Transport**

#### **GARD Chemicals**

Larragard Limited  
Chapel Lane,  
Heckmondwike,  
West Yorkshire WF16 9JP

**T** +44 (0) 1924 403550  
**F** +44 (0) 1924 400999  
**E** [sales@gardchemicals.com](mailto:sales@gardchemicals.com)  
**W** [www.gardchemicals.com](http://www.gardchemicals.com)

