



## SAFETY DATA SHEET

### Tuskbond SC12 Solvent Cleaner Aerosol

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Tuskbond SC12 Solvent Cleaner Aerosol

**Container size** 500ml

**EU REACH registration notes** All chemicals used in this product have been registered under REACH where required.

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cleaning Solvent.

**Uses advised against** Use only for intended applications.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Tuskbond  
Shelley Close  
Lowmoor Business Park  
Kirkby in Ashfield  
NG17 7JZ  
Tel: 01623 722661 (Mon-Fri 09:00-17:00)  
Fax: 01623 885971  
Email: SDS@sangler.org.uk

##### 1.4. Emergency telephone number

**Emergency telephone** UK +44 (0) 1623 722661 (Mon-Fri 09:00-17:00)

**National emergency telephone number** IN AN EMERGENCY DIAL 999 / 112  
For non-emergencies, call NHS 111 (24/7) or a doctor

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (SI 2019 No. 720)

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 2 - H411

##### 2.2. Label elements

###### Hazard pictograms



**Signal word**

Danger

## Tuskbond SC12 Solvent Cleaner Aerosol

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
<b>Contains</b>	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, ACETONE
<b>Supplementary precautionary statements</b>	P261 Avoid breathing spray. P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.

### 2.3. Other hazards

Containers should be thoroughly emptied before disposal because of the risk of an explosion. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. In use may form flammable/explosive vapour-air mixture. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>	<b>30-60%</b>
<b>(&lt;0.1% 1,3 BUTADIENE)</b>	
CAS number: 68476-85-7	EC number: 270-704-2
<b>Classification</b>	
Flam. Gas 1A - H220	
Press. Gas (Liq.) - H280	

## Tuskbond SC12 Solvent Cleaner Aerosol

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	<b>30-60%</b>
CAS number: —	EC number: 921-024-6
<b>Classification</b>	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
<b>ACETONE</b>	<b>10-30%</b>
CAS number: 67-64-1	EC number: 200-662-2
<b>Classification</b>	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

**Composition comments** Liquefied petroleum gases (CAS: 68476-85-7) contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. If breathing stops, provide artificial respiration. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Get medical attention. Do not induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Inhalation</b>	Coughing, chest tightness, feeling of chest pressure. Exposure may cause coughing or wheezing. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
<b>Ingestion</b>	There may be soreness and redness of the mouth and throat.

## Tuskbond SC12 Solvent Cleaner Aerosol

**Skin contact** Prolonged contact may cause redness, irritation and dry skin. Product has a defatting effect on skin.

**Eye contact** There may be irritation and redness. Eyes may water profusely. Irritating to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Show this safety data sheet to the doctor in attendance. The following symptoms may occur: Nausea, headache, dizziness, coughing and breathing difficulty.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Water spray, dry powder or carbon dioxide. Alcohol-resistant foam.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

**Hazardous combustion products** Oxides of carbon. Acrid smoke or fumes.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not breathe vapour. Avoid contact with eyes and prolonged skin contact.

**For non-emergency personnel** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

**For emergency responders** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

### 6.2. Environmental precautions

**Environmental precautions** Contain the spillage using bunding. Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Approach the spillage from upwind. Take precautionary measures against static discharge. Use only non-sparking tools.

### 6.4. Reference to other sections

## Tuskbond SC12 Solvent Cleaner Aerosol

**Reference to other sections** For personal protection, see Section 8. See Section 7 for information on safe handling. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Wear protective clothing as described in Section 8 of this safety data sheet. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using this product.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work area every day.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Store away from the following materials: Alkalis. Protect from sunlight. Do not pierce or burn, even after use. Do not expose to temperatures exceeding 50°C/122°F.

**Storage class** Extremely Flammable Aerosol

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**Usage description** Store in a flammable storage cupboard according to national regulations. Solvent based aerosol.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

##### **DNEL**

Consumer - Oral; Long term systemic effects: 699 mg/kg/day

Workers - Oral; Long term systemic effects: 2035 mg/kg/day

Consumer - Dermal; Long term systemic effects: 699 mg/kg/day

Workers - Dermal; Long term systemic effects: 773 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 608 mg/m<sup>3</sup>

##### **ACETONE (CAS: 67-64-1)**

## Tuskbond SC12 Solvent Cleaner Aerosol

<b>DNEL</b>	Workers - Dermal; Long term : 186 mg/kg/day Workers - Inhalation; Short term : 2420 mg/m <sup>3</sup> Workers - Inhalation; Long term : 1210 mg/m <sup>3</sup> Consumer - Oral; Long term : 62 mg/kg/day Consumer - Dermal; Long term : 62 mg/kg/day Consumer - Inhalation; Long term : 200 mg/m <sup>3</sup>
<b>PNEC</b>	Fresh water; 10.6 mg/l marine water; 1.06 mg/l Intermittent release; 21 mg/l Sediment (Freshwater); 30.4 mg/kg/day Sediment (Marinewater); 3.04 mg/kg/day Soil; 33.3 mg/kg/day STP; 100 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure. Refer to protective measures listed in sections 7 and 8.

#### Personal protection

Wear protective work clothing.

#### Eye/face protection

Wear chemical splash goggles. Personal protective equipment that provides appropriate eye and face protection should be worn.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. The breakthrough time for any glove material may be different for different glove manufacturers. It is recommended that gloves are made of the following material: Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH).

#### Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

#### Hygiene measures

Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. For short term use an AX filter is recommended.

## Tuskbond SC12 Solvent Cleaner Aerosol

<b>Thermal hazards</b>	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
<b>Environmental exposure controls</b>	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Colourless to pale yellow.
<b>Odour</b>	Acetone. Ketonic.
<b>Odour threshold</b>	Not available.
<b>pH</b>	pH (concentrated solution): 7
<b>Melting point</b>	No information required.
<b>Initial boiling point and range</b>	Liquefied petroleum gases: -40 to -2°C Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane: 60 to 100°C Acetone: 56°C
<b>Flash point</b>	A flash point method is not available but the major hazardous component, the liquefied petroleum gases, has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
<b>Evaporation rate</b>	Not available.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	No information required.
<b>Vapour pressure</b>	4 - 6 bar @ 20°C
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Liquid base: 0.65 - 0.75 @ 20°C
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Liquefied petroleum gases: 365°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Liquid base: Kinematic viscosity ≤ 20.5 mm <sup>2</sup> /s.
<b>Explosive properties</b>	In use may form flammable/explosive vapour-air mixture.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.
<b>9.2. Other information</b>	
<b>Particle size</b>	No information required.
<b>Volatile organic compound</b>	621g/l

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	Stable under recommended transport or storage conditions.
-------------------	---

#### 10.2. Chemical stability

## Tuskbond SC12 Solvent Cleaner Aerosol

**Stability** Stable at normal ambient temperatures and when used as recommended. Highly volatile.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not polymerise. In use may form flammable/explosive vapour-air mixture.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas.

### 10.5. Incompatible materials

**Materials to avoid** Strong acids. Strong oxidising agents. Strong alkalis.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**Summary** Based on available data the classification criteria are not met.

#### Acute toxicity - dermal

**Summary** Based on available data the classification criteria are not met.

#### Acute toxicity - inhalation

**Summary** Based on available data the classification criteria are not met.

#### Skin corrosion/irritation

**Summary** Causes skin irritation.

#### Serious eye damage/irritation

**Summary** Causes serious eye irritation.

#### Respiratory sensitisation

**Summary** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Summary** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Summary** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Summary** Based on available data the classification criteria are not met.

#### Reproductive toxicity

**Summary** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**Summary** May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

**Summary** Based on available data the classification criteria are not met.

#### Aspiration hazard



## Tuskbond SC12 Solvent Cleaner Aerosol

**Summary** Based on available data the classification criteria are not met.

### Toxicological information on ingredients.

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

<b>Toxicological effects</b>	Information given is based on data of the components and of similar products.
<b><u>Acute toxicity - oral</u></b>	
<b>Notes (oral LD<sub>50</sub>)</b>	Not applicable.
<b><u>Acute toxicity - dermal</u></b>	
<b>Notes (dermal LD<sub>50</sub>)</b>	Not applicable.
<b><u>Acute toxicity - inhalation</u></b>	
<b>Notes (inhalation LC<sub>50</sub>)</b>	LC <sub>50</sub> >20 mg/l, Inhalation, Rat
<b><u>Skin corrosion/irritation</u></b>	
<b>Skin corrosion/irritation</b>	Not irritating.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Not irritating.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	Not sensitising.
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Not sensitising.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	This substance has no evidence of mutagenic properties.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Carcinogenicity in humans is not expected.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Does not contain any substances known to be toxic to reproduction.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Not anticipated to present an aspiration hazard, based on chemical structure.
<b>Inhalation</b>	May cause respiratory system irritation.

## Tuskbond SC12 Solvent Cleaner Aerosol

**Skin contact** Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

**Route of exposure** Inhalation Skin and/or eye contact

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rabbit

#### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 20.0

**Species** Rat

#### Skin corrosion/irritation

**Skin corrosion/irritation** Skin irritation.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

#### Aspiration hazard

**Aspiration hazard** May be fatal if swallowed and enters airways.

### ACETONE

## Tuskbond SC12 Solvent Cleaner Aerosol

**Toxicological effects** The toxicity of this substance has been assessed during REACH registration.

### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,800.0

**Species** Rat

**ATE oral (mg/kg)** 5,800.0

### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 15,800.0

**Species** Rat

**ATE dermal (mg/kg)** 15,800.0

### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 76.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 76.0

### Skin corrosion/irritation

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

### Skin sensitisation

**Skin sensitisation** Not sensitising. Guinea pig

### Germ cell mutagenicity

**Genotoxicity - in vitro** Gene mutation: Negative.

**Genotoxicity - in vivo** Micronucleus assay: Negative.

### Reproductive toxicity

**Reproductive toxicity - development** No evidence of reproductive toxicity in animal studies.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOAEL 900 mg/kg/90d bw/d, Oral, Rat  
NOAEC 22500 mg/m<sup>3</sup>/8w, Inhalation, Rat

## SECTION 12: Ecological information

**Ecotoxicity** The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

### Ecological information on ingredients.

**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)**

## Tuskbond SC12 Solvent Cleaner Aerosol

**Ecotoxicity** Information given is based on data of the components and of similar products.

### 12.1. Toxicity

**Toxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Ecological information on ingredients.

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

**Toxicity** Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, : 10-100 mg/l, Fish  
NOEC, : 1-10 mg/l, Fish

**Acute toxicity - aquatic invertebrates** LC<sub>50</sub>, : 1-10 mg/l, TISBE Marine copepod  
NOEC, : 0.1-1 mg/l, TISBE Marine copepod

**Acute toxicity - aquatic plants** LC<sub>50</sub>, : 10-100 mg/l, Algae

#### ACETONE

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 8800 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** NOEC, 8 hours: 530 mg/l/8 d, Algae

**Acute toxicity - microorganisms** EC<sub>12</sub>, 30 min: 1000 mg/l, Activated sludge

**Acute toxicity - terrestrial** LD<sub>50</sub>, 48 hours: 0.1 - 1 mg/cm<sup>2</sup>, Eisenia Fetida (Earthworm)

#### Chronic aquatic toxicity

**Chronic toxicity - aquatic invertebrates** NOEC, 28 days: 2212 mg/l, Daphnia magna

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### Ecological information on ingredients.

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

**Persistence and degradability** The product is readily biodegradable.

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Persistence and degradability** The substance is readily biodegradable.

## Tuskbond SC12 Solvent Cleaner Aerosol

### ACETONE

<b>Persistence and degradability</b>	The product is readily biodegradable.
<b>Biodegradation</b>	Water - Degradation 91: 28 days
<b>Chemical oxygen demand</b>	2.21 g O <sub>2</sub> /g substance

#### 12.3. Bioaccumulative potential

<b>Bioaccumulative potential</b>	Readily evaporates from water/soil due to high volatility.
<b>Partition coefficient</b>	Not available.

#### Ecological information on ingredients.

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

<b>Bioaccumulative potential</b>	Bioaccumulation is unlikely.
----------------------------------	------------------------------

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

<b>Bioaccumulative potential</b>	Not available.
<b>Partition coefficient</b>	log Pow: 3.4 - 5.2

### ACETONE

<b>Bioaccumulative potential</b>	BCF: 3, Estimated value.
----------------------------------	--------------------------

#### 12.4. Mobility in soil

<b>Mobility</b>	Volatile
-----------------	----------

#### Ecological information on ingredients.

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

### ACETONE

<b>Mobility</b>	Mobile.
<b>Adsorption/desorption coefficient</b>	Soil - Kd: 1.5 L/kg @ 20°C
<b>Henry's law constant</b>	2.929 - 2.070 Pa m <sup>3</sup> /mol @ 25°C water 3.311 Pa m <sup>3</sup> /mol @ 25°C marine water

#### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	Not determined
---	----------------

#### Ecological information on ingredients.

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

<b>Results of PBT and vPvB assessment</b>	This product does not contain any substances classified as PBT or vPvB.
---	---

## Tuskbond SC12 Solvent Cleaner Aerosol

### ACETONE

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current UK criteria.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

#### Ecological information on ingredients.

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Other adverse effects** The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	Ensure containers are empty before discarding (explosion risk). Must not be disposed of together with household waste.
<b>Disposal methods</b>	Do not puncture or incinerate, even when empty. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
<b>Waste class</b>	Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

### SECTION 14: Transport information

#### 14.1. UN number

<b>UN No. (ADR/RID)</b>	1950
<b>UN No. (IMDG)</b>	1950
<b>UN No. (ICAO)</b>	1950
<b>UN No. (ADN)</b>	1950

#### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	AEROSOLS
<b>Proper shipping name (IMDG)</b>	AEROSOLS, MARINE POLLUTANT (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
<b>Proper shipping name (ICAO)</b>	AEROSOLS
<b>Proper shipping name (ADN)</b>	AEROSOLS

#### 14.3. Transport hazard class(es)

<b>ADR/RID class</b>	2.1
<b>ADR/RID classification code</b>	5F
<b>ADR/RID label</b>	2.1
<b>IMDG class</b>	2.1
<b>ICAO class/division</b>	2.1

## Tuskbond SC12 Solvent Cleaner Aerosol

**ADN class** 2.1

### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**



### 14.6. Special precautions for user

**IMDG Code segregation group** SG69, SW1, SW22

**EmS** F-D, S-U

**ADR transport category** 2

**Tunnel restriction code** (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).  
Control of Substances Hazardous to Health Regulations 2002 (as amended).  
Health and Safety at Work etc. Act 1974 (as amended).

**Guidance** Workplace Exposure Limits EH40.

**Authorisations (SI 2020 No. 1577 Annex XIV)** No specific authorisations are known for this product.

**Restrictions (SI 2020 No. 1577 Annex XVII)** No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

**Classification procedures according to SI 2019 No. 720** Aerosol 1 - H222, H229: Weight of evidence. Skin Irrit. 2 - H315: Calculation method. Eye Irrit. 2 - H319: Calculation method. STOT SE 3 - H336: Calculation method. Aquatic Chronic 2 - H411: Calculation method.

**Issued by** Technical Department

**Revision date** 17/06/2021

## Tuskbond SC12 Solvent Cleaner Aerosol

<b>Revision</b>	5.1
<b>Supersedes date</b>	22/01/2019
<b>SDS number</b>	21616
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.