

## TECHNICAL DATA SHEET

### HIGH TACK ADHESIVE

TYPE:	SEMI PERMANENT PRESSURE SENSITIVE
PROPERTIES:	COLOUR: CLEAR – ODOUR: SWEETISH
SUGGESTED USE	PAPER, PLASTIC, ETC. USE ON LIGHTWEIGHT OBJECTS WHERE SOME RELEASE PROPERTIES ARE REQUIRED.
CHARACTERISTICS:	SOFT ADHESIVE WITH MEDIUM PEEL STRENGTH AND MEDIUM SHEAR STRENGTH.
TEMPERATURE RANGE:	-10 TO 60°C. DUE TO VARIATION IN THE SIZE OF THE DOTS, AND NATURE OF THE TESTING, RESULTS SHOULD BE TREATED AS APPROXIMATE.
SUGGESTED HANDLING:	READY FOR USE AS SUPPLIED. KEEP AWAY FROM DUST, OIL, AND ULTRAVIOLET LIGHT
PRECAUTIONS:	THIS PRODUCT CONTAINS SOME OIL; TEST ABSORBANT SURFACES FOR BLEEDING.
SHELF LIFE:	USE OLDEST STOCK FIRST. THIS PRODUCT SHOULD BE STORED IN A DUST FREE ENVIRONMENT AND IN A COOL DRY PLACE. DISCARD UNUSED PRODUCT AFTER 18 MONTHS. THIS PRODUCT CONTAINS SOME OIL

We are available to help purchasers obtain best results from information believed to be reliable. However we have no control over the conditions under which our products are transported, stored, handled or used by Purchasers and in any event all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use.